



The "ENDURO" engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

E85AETL/E85AETX



TECHNICAL CHARACTERISTICS	E85AETL	E85AETX
MOTOR		
Engine Type	In-line 2	In-line 2
Reduction ratio	5.1 :1	5.1 :1
Start-up	Electric	Électrique
Power system	3 Carburetors	3 Carburetors
Lubrication system	Pre-Mixing 2 %	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	35.0 L/h @5500 r/min	35.0 L/h @5500 r/min
Fuel	Regular Gasoline	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500	4500-5500
Max.Prop Shaft Horsepower (Kw)	62.5 (85 hp)	62.5 (85 hp)
Bore x Stroke (mm)	82.0 X 72.0	82.0 X 72.0
Architecture	L3	L3
Displacement (cc)	1140	1140
MORE		
Propeller Rotation	Clockwise	Clockwise
Alternator	10 A	10 A
Control	Remote Control	Remote Control
DIMENSIONS		
Engine transom height (mm)	L : 521 (20.5 in)	X : 647 (25.5 in)
Dry weight with propeller (kg)	124	124
EQUIPMENTS		
Service kit assy.	✓	✓
Fuel Tank comp.	✓	✓
Fuel Pipe Comp.	✓	✓
Remocon Control	✓	✓
14ft Cable Remocon	✓	✓
REGULAR PROPELLER (3 blades)		
Material	ALUMINUM	ALUMINUM
Diameter	13 1/4	13 1/4

Always wear a helmet, eye protection and protective proper clothing.
CAMI encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

