F250HETX/FL250HETX



The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F250HETX	FL250HETX
MOTOR		
Displacement (cc)	3352	3352
Architecture	V6	V6
Bore x Stroke (mm)	94.0 X 80.5	94.0 X 80.5
Full throttle operating range (tr/min)	5000-6000	5000-6000
Fuel	Wet Sump	Wet Sump
Fuel consumption (L/h-tr/min)	75.6 L/h @5500 r/min	75.6 L/h @5500 r/min
Lubrication system	Unleaded	Unleaded
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Reduction ratio	9.9 :1	9.9 :1
Number of Displacement	-	
Maximum Power (Kw)	-	
Ignition System	Electronic Ignition (TCI)	Electronic Ignition (TCI)
Gear Ratio		-
Steering Control		
Reverse direction		
Trim method (positions)	-	MOTODS
Engine Type	4-stroke engine - V6	4-stroke engine - V6
Start-up	Electric with Prime Start™	Electric with Prime Start™
Max.Prop Shaft Horsepower (Kw)	183.9 (250 hp)	183.9 (250 hp)
MORE		
Control	Remote Control	Remote Control
Alternator	46 A	46 A
Propeller Rotation	Clockwise	Counter clockwise
DIMENSIONS		
Engine Oil Capacity (L)	-	-
Oil capacity (L)	4.7 L / 4.5 L	4.7 L /4.5 L
Engine transom height (mm)	X : 643 (25.3 inch)	X : 643 (25.3 inch)
Dry weight with propeller (kg)	289	289
EQUIPMENT	F250HETX	FL250HETX
Service kit assy.	✓	✓
Fuel Tank comp.	-	-
Fuel Pipe Comp.	-	-
Remocon Control	✓	✓
14ft Cable Remocon	-	
		-

20ft Cable Remocon	-	-
Cable end, Remote control	✓	✓
Tachometer	-	-
Trim Meter	-	-
Panel Switch	✓	✓
Ride, Guide Kit Twin	-	-
Multi Display	✓	-
Speedo Assy.	-	-
Fuel Meter Movement	-	-
Kill Switch	-	-
REGULAR PROPELLER (3 blades)	F250HETX	FL250HETX
Material	STEEL	STEEL
Diameter	14 1/2	14 1/2

Always wear a helmet, eye protection and protective proper clothing. CAMI encourages you to ride safely with responsible manners that comply with all laws while respecting the environment

