



The "ENDURO" engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

## EK40GMHL



TECHNICAL CHARACTERISTICS	EK40GMHL
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	5.0 :1
Start-up	Manual
Power system	1 Dual Throat Carburetors
Lubrication system	Pre-Mixing 3 %
Fuel consumption (L/h-tr/min)	19.5 L/h @5500 r/min
Fuel	Kerosene
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	29.4 (40 hp)
Bore x Stroke (mm)	78.0 X 70.0
Architecture	L2
Displacement (cc)	669
<b>MORE</b>	
Propeller Rotation	Sens Horaire
Alternator	80W
Control	Tiller handle
<b>DIMENSIONS</b>	
Engine transom height (mm)	L: 571 (22.5 in)
Dry weight with propeller (kg)	68
<b>EQUIPMENTS</b>	
Service kit assy.	✓
Fuel Tank comp.	✓
Fuel Pipe Comp.	✓
<b>REGULAR PROPELLER (3 blades)</b>	
Material	ALUMINUM
Diameter	11 1/2

Always wear a helmet, eye protection and protective proper clothing.  
CAMI encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

