



F150FETX/FL150FETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F150FETX	FL150FETX
MOTOR		
Engine Type	In-line 4	In-line-4
Ignition System	Electronic Ignition (TCI)	Allumage Électronique (TCI)
Reduction ratio	9.0 :1	9.0 :1
Start-up	Electric with Prime Start™	Electric with Prime Start™
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	56.3 L/h @5000 r/min	56.3 L/h @5000 tr/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	4500-5500	4500-5500
Max.Prop Shaft Horsepower (Kw)	110.3 (150 hp)	110.3 (150 hp)
Bore x Stroke (mm)	94.0 X 96.2	94.0 X 96.2
Architecture	L4	L4
Displacement (cc)	2670	2670
MORE		
Propeller Rotation	Clockwise	Counter Clockwise
Alternator	35 A	35 A
Control	Remote Control	Remote Control
DIMENSIONS		
Dry weight with propeller (kg)	223	223
Engine transom height (mm)	X : 643 mm	X : 643 mm
Oil capacity (L)	4.5 L / 4.3 L	4.5 L / 4.3 L

Always wear a helmet, eye protection and protective proper clothing.
CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

