



F200BETX/FL200BETX

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F200BETX	FL200BETX
MOTOR		
Engine Type	4-stroke engine - V6	4-stroke engine - V6
Ignition System	Electronic Ignition (TCI)	Electronic Ignition (TCI)
Reduction ratio	9.9 :1	9.9 :1
Start-up	Electric with Prime Start™	Electric with Prime Start™
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	73.7 L/h @5500 r/min	73.7 L/h @5500 r/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	5000-6000	5000-6000
Max.Prop Shaft Horsepower (Kw)	147.1 (200 hp)	147.1 (200 hp)
Bore x Stroke (mm)	94.0 X 80.5	94.0 X 80.5
Architecture	V6	V6
Displacement (cc)	3352	3352
MORE		
Propeller Rotation	Sens Horaire	Counter Clockwise
Alternator	46 A	46 A
Control	Remote Control	Remote Control
DIMENSIONS		
Dry weight with propeller (kg)	289	289
Engine transom height (mm)	X : 643 (25.3 inch)	X : 643 (25.3 inch)
Oil capacity (L)	4.7 L/4.5 L	4.7 L/4.5 L
EQUIPMENT		
Service kit assy.	✓	✓
Remocon Control	✓	✓
Tachometer	✓	✓
Panel Switch	-	✓
Ride, Guide Kit Twin	-	✓
Speedo Assy.	✓	-
Fuel Meter Movement	-	✓
REGULAR PROPELLER (3 blades)		
Material	STEEL	STEEL
Diameter	14 1/2	14 1/2

Always wear a helmet, eye protection and protective proper clothing.

CAMI encourages you to ride safely with your Yamaha outboard motor, protecting the environment.



