



F300DET/FL300DET

The Africa 4-stroke range, born from monitoring and Yamaha's long experience, has been specially developed to meet the extreme conditions of use. Power and reliability are the hallmarks of this range of engines in a field where Yamaha is the reference brand.



TECHNICAL CHARACTERISTICS	F300BETX	FL300BETX
MOTOR		
Engine Type	4-stroke engine - V6	4-stroke engine - V6
Ignition System	Electronic Ignition (TCI)	Electronic Ignition (TCI)
Reduction ratio	10.3 :1	10.3 :1
Start-up	Electric with Prime Start™	Electric with Prime Start™
Power system	Electronic Injection (EFI)	Electronic Injection (EFI)
Lubrication system	Unleaded	Unleaded
Fuel consumption (L/h-tr/min)	96.6 L/h @5500 r/min	96.6 L/h @5500 r/min
Fuel	Wet Sump	Wet Sump
Full throttle operating range (tr/min)	5000-6000	5000-6000
Max.Prop Shaft Horsepower (Kw)	220.6 (300 hp)	220.6 (300 hp)
Bore x Stroke (mm)	96.0 X 96.0	96.0 X 96.0
Architecture	V6	L4
Displacement (cc)	4169	4169
MORE		
Propeller Rotation	Clockwise	Counter Clockwise
Alternator	70 A	70 A
Control	Remote Control	Remote Control
DIMENSIONS		
Dry weight with propeller (kg)	268	268
Engine transom height (mm)	X : 643 (25.3 inch)	X : 643 (25.3 inch)
Oil capacity (L)	6.3 L/ 6.0 L	6.3 L/6.0 L
EQUIPMENT		
Service kit assy.	✓	✓
Remocon Control	✓	✓
Panel Switch	✓	✓
Ride, Guide Kit Twin	-	✓
Multi Display	✓	-
REGULAR PROPELLER (3 blades)		
Material	STEEL	STEEL
Diameter	15 1/4	15 1/4

Always wear a helmet, eye protection and protective proper clothing.

CAMI encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

