



The "ENDURO" engines, true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme conditions of use, and it is no coincidence that YAMAHA Enduro engines are used in the vast majority of traditional fishing canoes.

## E150AETX



TECHNICAL CHARACTERISTICS	E150AETX
<b>MOTOR</b>	
Engine Type	In-line 2
Reduction ratio	6.2 :1
Start-up	Electric
Power system	3 Dual Throat Carburetors
Lubrication system	Pre-Mixing 2 %
Fuel consumption (L/h-tr/min)	72 l/h @5500 tr/min
Fuel	Regular Gasoline
Full throttle operating range (tr/min)	4500-5500
Max.Prop Shaft Horsepower (Kw)	110.3 (150 hp)
Bore x Stroke (mm)	90.0 X 68.0
Architecture	V6
Displacement (cc)	2596
<b>MORE</b>	
Propeller Rotation	Clockwise
Alternator	14 A
Control	Remote Control
<b>DIMENSIONS</b>	
Engine transom height (mm)	X : 642 (25.3 in)
Dry weight with propeller (kg)	184
EQUIPMENTS	E150AETX
Service kit assy.	✓
Remocon Control	✓
19ft Cable Remocon	✓
Cable end, Remote control	✓
Tachometer	✓
Trim Meter	✓
REGULAR PROPELLER (3 blades)	E150AETX
Material	STEEL
Diameter	13 3/4

Always wear a helmet, eye protection and protective proper clothing.  
CAMI encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

